

## XP100P



Lithium-Ion Powered

# NO MORE PUMPING!

Superior control with greater productivity

#### 7.2v LITHIUM-ION POWERED SPRAYER

Maintains optimum pressure range (16-23psi).

#### 18" BRASS WAND with PROVEN BRASS VALVE

Brass durability and pro-level performance.

### INCLUDES INTERCHANGEABLE 4-WAY and 50015ESS FAN NOZZLE

Meets labeling requirement for all formulations.

## HEAVY-DUTY 50" REINFORCED RUBBER & NYLON HOSE

Provides durabile dependable service.

#### 64" PRO SHOULDER STRAP with PAD

For all day comfort.

#### **VITON® SEALS**

Field tested for maximum compatability.

PUMP WALL CHARGER included.

#### **INCLUDES TANK CAP**

For safe storage and transport.





SPRAYER





CHEMICALLY

RESISTANT TO

FORMULATIONS

MODERN AGGRESSIVE



SPRAYS

UP TO 3hrs.

CONTINUOUSLY

PER CHARGE





# 1 Gal.

LITHIUM-ION **SPRAYER** 

Maintains flexibility for years of use.

Heavy-Duty 50" Reinforced Rubber & Nylon Hose.

Integrated Carry Handle

and Rubber Booted Power Switch and **Battery Status Light** and Charger Port.



#### 7.2v Lithium-ion

**Powered Compressor** provides Time Saving, **Consistent Uninterrupted** Pressure through-out your applications.

Re-pressurizing 2 minutes/gallon while spraving with a 3-hour run time.





**Tear-Drop Shaped Tank** for lower center of gravity to prevent accidental spills.

Integrated Wand Storage Keeps wand safely stored during transportation.

18" Brass Wand

with Comfort Grip and Internal Filter.

and Professional Shut-Off

Operational Superiority and ease of maintenance.

Pressure Release Valve

prevents "spray back" relieve pressure prior to opening.

64" Pro Shoulder Strap with Comfort Pad

for easy of operation and comfortable use.

Minimize one-hand carry freeing the use of both hands.

4-Way Brass Nozzle

for precise applications with coarse & fine fan, C&C straw and pin stream.

Also includes 50015ESS tip for full range spray coverage.

## *XP100P*

**High-Performance Application Equipment for Modern Technicians.** Designed by PCO Professionals for PCO Professionals on the foundation of Application Economics.

Specifications	XP100P
Empty Weight	6 LBS
Tank Capacity	1 Gallons
Wand	18" Brass
Nozzles	4-Way and 50015ESS
Hose Length	50" Nylon Reinforced
In-Valve Filter	Replaceable 250 Mesl
Pallet Quantity	45
Flow Rate	0.085 GPM at 20 PSI
Spray Duration Per Charge	UP TO 3 HOURS
Spray Volume Per Charge	20 GALLONS
UPC	8 41688 00692 8
<b>Key Service Parts</b>	

## & Accessories

Pump Zero Kit	184163
18" Wand	182874
4-Way Nozzle	182912
Shut-off Assembly	182867
Hose Assembly	182893
Pro Shoulder Strap	184536

Spray Patten Accuracy is fundamental to Safety, Efficiency and Compliance. The XP100P Technology makes you a better applicator by eliminating the fluctuation in spray patterns that manual pumps simply cannot.















**SCAN for more** Information

